

## DM6801A+ - Features and Benefits



- K type thermometer with large LCD display
- Strong antimagnetic and anti-jamming performance
- Data hold function
- High resolution:0.1°C/°F
- High stability, high accuracy: 0.2%
- CE certification

Specifications	Characteristics		
	Thermometer type	K type	
	Basic Function	Range	Basic Accuracy
	Centigrade temperature	-50°C~199.9°C	±(0.2%+1)
	Centigrade temperature	-50°C~1000°C	±(0.3%+1)
	Centigrade temperature	1000°C~1300°C	±(0.5%+1)
	Degree Fahrenheit	-50°F~199.9°F	±(0.3%+2)
Degree Fahrenheit	-50°F~1999°F	±(0.5%+2)	
Special Function			
Low battery indication	Approx. less than 7.5V		
Data hold	√		
Unit symbol display	√		
Function protect	√		
Anti-shock protect	√		
Input impedance	10MΩ		
Sampling rate	3 times/s		
Operation way	Manual range		
Max. display	1999		
LCD size	67x40mm		
Battery	9V (6F22)		
Power dissipation	Quiescent current approx. 3.5mA		
General Characteristic			
Color	Body-dark grey , holster-orange (Pantone No.:1495U)		
Dimension	130mm×95mm×28mm		
Weight	240g(including battery)		
Standard accessory	Battery, manual, TP01 K type temperature probe		
Packing	Gift box		
Standard packing per carton	60pcs		
Carton size	455mm×315mm×430mm		
Standard G.W per carton	20kg		