

DM6802A+ - Features and Benefits



- K type thermometer
- Large LCD display, easy reading
- Strong antimagnetic and anti-jamming performance
- Data hold,function protect and anti-shock protect
- High stability,high resolution: 0.4%
- Dual input

Specifications	Characteristics		
	Thermometer type	K type	
	Basic Function	Range	Basic Accuracy
	Centigrade temperature	-50°C~1000°C	±(0.3%+1)
	Centigrade temperature	1000°C~1300°C	±(0.5%+1)
	Degree Fahrenheit	-50°F~1999°F	±(0.3%+2)
	T1-T2	°C/°F	±[0.3%(T1-T2 reading)+2]
	Special Function		
	Low battery indication	Approx. less than 7.5V	
	Data hold	√	
Unit symbol display	√		
Function protect	√		
Anti-shock protect	√		
Input impedance	10MΩ		
Sampling rate	3 times/s		
Operation way	Manual range		
Max. display	1999		
LCD size	67x40mm		
Battery	9V (6F22)		
Power dissipation	Quiescent current approx. 3.5mA		
General Characteristic			
Color	Body-dark grey , holster-orange (Pantone No.:1495U)		
Dimension	130mm×95mm×28mm		
Weight	240g(including battery)		
Standard accessory	Battery, manual, TP01 K type temperature probe		
Packing	Gift box		
Standard packing per carton	60pcs		
Carton size	455mm×315mm×430mm		
Standard G.W per carton	20kg		