

JF Series - - Features and Benefits



- High precision loadcell, compact design
- Aluminum Alloy die cast base and ss platter
- Super bright LCD display with backlight
- RS232C Interface for data transfer
- Clear Glass Windshield as standard
- Over load protection, Bubble Level Adjustment, Under hook
- Multi Weighing unit conversation g/mg/ct/oz
- Check Weighing, Parts counting, percentage weighing
- CE approval



0.1mg Repeatability

Model	JF1004	JF1204	JF1804	JF2004	JF2204	JF3004	JF3104
Capacity	0-100g	0-120g	0-180g	0-200g	0-220g	0-300g	0-310g
Calibration	External Calibration / Internal Calibration (Two calibration options)						
Touch Screen	Optional						
Readability	0.1mg						
Linearity	±0.2mg						
Repeatability	±0.2mg						
Pan Size	Φ80mm						
Output Interface	RS232/USB						
Power Supply	Universal Adaptor AC110-240V						
Dimensions	340mm x 215mm x350mm						
Net Wight	6800g						

1mg Repeatability

Model	JF1003	JF2003	JF3003	JF5003	JF6003	JF8003	JF10003
Capacity	0-110g	0-210g	0-310g	0-510g	0-620g	0-800g	0-1000g
Calibration	External Calibration / Internal Calibration (Two calibration options)						
Touch Screen	Optional						
Readability	1mg						
Linearity	±2mg						
Repeatability	±2mg						
Pan Size	Φ90mm						
Output Interface	RS232						
Power Supply	Adaptor supplied AC110-240V						
Dimensions	340mm x 215mm x350mm						
Net Wight	6800g						