

FA Series -- Features and Benefits



- High precision loadcell, compact design
- Aluminum Alloy die cast base and ss platter
- Super bright LCD display with backlight
- RS232C Interface for data transfer
- Multi Weighing unit conversation g/mg/ct/oz
- Check Weighing, Parts counting, percentage weighing
- Universal power adaptorsupplied as standard
- Certificated calibration weight supplied as standard
- CE approval



0.1mg Repeatability

Model	FA1004	FA1204	FA1604	FA2004	FA2204	FA3004	FA3204
Capacity	0-100g	0-120g	0-160g	0-200g	0-220g	0-300g	0-320g
Calibration	External Calibration / Internal Calibration (Two calibration options)						
Touch Screen	Optional						
Readability	0.1mg						
Linearity	±0.2mg						
Repeatability	±0.2mg						
Pan Size	Φ80mm						
Output Interface	RS232/USB						
Power Supply	Universal Adaptor AC110-240V						
Dimensions	340mm x 215mm x350mm						
Net Wight	6800g						

1mg Repeatability

Model	FA1003	FA2003	FA3003	FA5003	FA6003	FA8003	FA10003
Capacity	0-110g	0-210g	0-310g	0-510g	0-620g	0-800g	0-1000g
Calibration	External Calibration / Internal Calibration (Two calibration options)						
Touch Screen	Optional						
Readability	1mg						
Linearity	±2mg						
Repeatability	±2mg						
Pan Size	Φ90mm						
Output Interface	RS232						
Power Supply	Adaptorsupplied universal de la energía AC110-240V						
Dimensions	340mm x 215mm x350mm						
Net Wight	6800g						