

AG-126 Series - - Features and Benefits



- All intelligent design, rapid measurement
- Has voltage undervoltage indication function
- During operation will be issued a prompt tone
- Accurate measurement, good repetitiveness
- Use USB data output with connection PC(optional)
- Provide Bluetooth data output choice(optional)

OverView

The Glossmeter applies to Ink, paint, paint, paint, decoration materials, wood,marble,granite,polishing brick,tile measurement,paper and other non-metallic materials surface gloss test. Glossmeter have different kinds of measurement angles. Generally, 20°applies to High Gloss Materials, 60°applies to Medium Gloss Materials, 85°applies to Low Gloss Materials. Two additional angles are used for other materials. An angle of 45°is specified for the measurement of ceramics, films, textiles and anodised aluminium, whilst 75°is specified for paper and printed materials.

	Model	AG-126B	AG-1268B
Main Specifications	Measuring Angles	20°, 60°	20°, 60°, 85°
	Measuring Range	0.1 ~ 200 GU	
	Stability	±0.4GU/30Min	
	Error	< ± 1.2GU	
	Accuracy	±1.0 gloss unit (against reference standard)	
	Resolution	0.1 GU	
	Repeatability	±0.5 GU	
	Environment Temperature	0°C~40°C	
	Relative Humidity	No more than 85%	
	Power Supply	Built-in 3.7V lithium Battery	
	Dimensions	136mm*44mm*78mm	
Weight	350g (Including Batteries)		

Buying Guide

When you choose the model number of Amittari instrument, the default is standard delivery. If you need other optional accessories, please tell our customer -service worker.

The following three items are basic optional accessories choices

Standard Accessories+**USB** data output

Standard Accessories+**Bluetooth** data output

Standard Accessories

- Main Unit
- Carrying Case
- Operation Manual
- Holder with calibration standard
- Optic cleaning cloth
- Power adapter

Optional Accessories

- USB data output
- RS-232 Data Output
- Bluetooth data output